

# NEXT-PSE4809AT

## I PoE 인젝터



### • 제품개요 및 특징

NEXT-PEG4809AT Single-port Active PoE Injector는 100~240V AC전원을 인가하여 PoE를 위한 52V DC/ 500mA를 제공합니다. UTP 케이블의 1,2번 & 3,6번 연선을 통해서 54V DC의 전원이 공급되며, 안정적인 전력 공급을 위해 최대 30W의 출력을 지원합니다.

### • 세부스펙

제품인증 번호 : MSIP-REI-NXT-NEXT-POE4807J6

| Item                       | Description                                                                                                                                                                         |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| No. of channels            | 1                                                                                                                                                                                   |
| Pass Through Data Rates    | 10/100/1000 Mbps                                                                                                                                                                    |
| Power over Ethernet Output | Pin Assignment and Polarity : 1/2 (-), 3/6 (+)<br>Ourput Power Voltage : 54 V <sub>DC</sub><br>User Port Power : 30W max                                                            |
| Input Power Requierements  | AC Input Voltage : 100 to 240 V <sub>AC</sub><br>AC Input Current : 0.5A 100-240 V <sub>AC</sub><br>AC Frequency : 50 to 60Hz                                                       |
| Dimension                  | 118mm x 48mm x 34mm                                                                                                                                                                 |
| Indicators                 | System Indicator : AC Power<br>User Indicator : Channel Power                                                                                                                       |
| Connectors                 | Shielded RJ-45, EIA 568A and 568B                                                                                                                                                   |
| Protection                 | Over current protection<br>Over load protection<br>Over voltage protection<br>Anti-interfernce protection                                                                           |
| Environmental Conditions   | Operating Ambient Temperature : 0 to 40 °C<br>Operating Humidity : Maxium 90%, Non-condensing<br>Storage Temperature : -40 to 70°C<br>Storage Humidity : Maxium 90%, Non-condensing |
| Regulatory Compliance      | IEEE 802.3af (PoE) / IEEE 802.3at (PoE+)                                                                                                                                            |

### • Dimensions



### • 품목 정보

제조사/수입자 (주)이지넷유비쿼터스  
허가 관련 MSIP-REI-NXT-NEXT-POE4807J6